

# (12) UK Patent Application (19) GB (11) 2 370 978 (13) A

(43) Date of A Publication 17.07.2002

(21) Application No 0118379.7

(22) Date of Filing 27.07.2001

(30) Priority Data

(31) 01001617

(32) 11.01.2001

(33) KR

(71) Applicant(s)

**Samsung Kwangju Electronics Co., Ltd.**  
(Incorporated in the Republic of Korea)  
271 Oseon-dong, Kwangsan-gu, Kwangju-city,  
Republic of Korea

(72) Inventor(s)

**Jang-keun Oh**

(74) Agent and/or Address for Service

**Withers & Rogers**  
Goldings House, 2 Hays Lane, LONDON, SE1 2HW,  
United Kingdom

(51) INT CL<sup>7</sup>

**A47L 9/16**

(52) UK CL (Edition T )

**A4F FFD**

(56) Documents Cited

**EP 0928594 A**

**WO 00/74547 A**

**US 6146434 A**

**US 4172710 A**

(58) Field of Search

**UK CL (Edition S ) A4F FFD**

**INT CL<sup>7</sup> A47L 9/16**


**Online: WPI EPODOC JAPIO**

(54) Abstract Title

**Vacuum cleaner**

(57) An upright-type vacuum cleaner has a suction brush (50) and a cleaner body (20) having an upper dust chamber (21), a lower motor chamber (22) housing a motor, an air inflow path (25), and an air outflow path (26, 23a, 23b) interconnecting the dust chamber and the motor chamber. A cyclone body (31) is mounted in the dust chamber, and a dust barrel (37) removably mounted to a lower side of the cyclone body. The vacuum cleaner further includes a fine dust filtering portion (40) removably disposed in the air outflow path. The vacuum cleaner also includes a locking and unlocking device (6) which detaches the dust barrel (37) from the cyclone body (31). Accordingly, the user can dispose of collected contaminants and dust without having to remove the entire cyclone dust collecting apparatus (30), but rather by removing only the dust barrel (37) from the dust chamber (21).

FIG.2





GB 2 370 978 A

## Vacuum cleaner

**Patent number:** GB2370978  
**Publication date:** 2002-07-17  
**Inventor:** OH JANG-KEUN (KR)  
**Applicant:** SAMSUNG KWANGJU ELECTRONICS CO (KR)  
**Classification:**  
- **international:** A47L9/16  
- **european:** A47L9/16  
**Application number:** GB20010018379 20010727  
**Priority number(s):** KR20010001617 20010111

**Also published as:**

 US6732406 (B2)  
 US2002088079 (A1)

**Abstract of GB2370978**

An upright-type vacuum cleaner has a suction brush (50) and a cleaner body (20) having an upper dust chamber (21), a lower motor chamber (22) housing a motor, an air inflow path (25), and an air outflow path (26, 23a, 23b) interconnecting the dust chamber and the motor chamber. A cyclone body (31) is mounted in the dust chamber, and a dust barrel (37) removably mounted to a lower side of the cyclone body. The vacuum cleaner further includes a fine dust filtering portion (40) removably disposed in the air outflow path. The vacuum cleaner also includes a locking and unlocking device (6) which detaches the dust barrel (37) from the cyclone body (31). Accordingly, the user can dispose of collected contaminants and dust without having to remove the entire cyclone dust collecting apparatus (30), but rather by removing only the dust barrel (37) from the dust chamber (21).



---

Data supplied from the **esp@cenet** database - Worldwide

## Vacuum cleaner

**Patent number:** GB2370978  
**Publication date:** 2002-07-17  
**Inventor:** OH JANG-KEUN (KR)  
**Applicant:** SAMSUNG KWANGJU ELECTRONICS CO (KR)  
**Classification:**  
- **international:** A47L9/16  
- **european:** A47L9/16  
**Application number:** GB20010018379 20010727  
**Priority number(s):** KR20010001617 20010111

**Also published as:**

 US6732406 (B2)  
 US2002088079 (A1)

**Abstract of GB2370978**

An upright-type vacuum cleaner has a suction brush (50) and a cleaner body (20) having an upper dust chamber (21), a lower motor chamber (22) housing a motor, an air inflow path (25), and an air outflow path (26, 23a, 23b) interconnecting the dust chamber and the motor chamber. A cyclone body (31) is mounted in the dust chamber, and a dust barrel (37) removably mounted to a lower side of the cyclone body. The vacuum cleaner further includes a fine dust filtering portion (40) removably disposed in the air outflow path. The vacuum cleaner also includes a locking and unlocking device (6) which detaches the dust barrel (37) from the cyclone body (31). Accordingly, the user can dispose of collected contaminants and dust without having to remove the entire cyclone dust collecting apparatus (30), but rather by removing only the dust barrel (37) from the dust chamber (21).

---

Data supplied from the **esp@cenet** database - Worldwide